



Performance Beast Plus

Performance Beast Plus is the ideal floor for power, strength and functional training applications. This 14.5mm performance floor features a 2.5mm Vulcanized Composition Rubber (VCR) surface fusion bonded to a 12mm base layer using itsTRU™ technology. The result is a floor designed to withstand extreme weight impacts while minimizing bar bounce. Using Performance Beast Plus with our Performance Rally and/or TurfX creates the ideal fitness floor solution without transitions.



MARKETS

- Fitness
- Student Rec
- Sports

APPLICATIONS

- Selectorized Strength
- Free Weights
- Functional Training
- Olympic Style Lifting

BENEFITS

- Durable
- Sustainable
- Slip resistant
- Ease of maintenance

PRODUCT INFORMATION

Nominal Dimensions:

Available as a standard in rolls. Talk to your local sales rep to determine availability, pricing, minimums, and lead times.



14.5mm (2.5mm + 12mm) x 48" (1.2m)

Color Options:

[Click here to view colors](#)

TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Static Load Limit	ASTM F970	0.008" @250 psi
Coefficient of Friction	ASTM D2047	> 0.9
Abrasion Resistance	ASTM D3389	< 1g, 1,000 cycles
Pill Test	ASTM D2859	Pass
Force Reduction	Deltec	17.4%
Energy Restitution	Deltec	66.3%
Impact Insulation Class*	ASTM E492	55
Delta IIC*	ASTM E2179	25

*Tested on a 6" concrete slab with no ceiling.

THE NRG FACTOR

NRG =



17.4%

Force Reduction
Absorption of impact energy



66.3%

Energy Restitution
Useful return of impact energy



Safety



Ergonomics



Acoustics

